







- Hydraulic Hose Skiving M/c.
- Morizontal Hydraulic Hose Crimping M/c.
- Horizontal Hose Crimping M/c.
- Low Pressure Hose Crimping M/c.
- Vertical Hose Crimping M/c.






ABOUT US

Devanshi Electro-Mech is established in the year 2001. We, Devanshi Hydromatic Inc., are involved in manfuacturing, supply and exporting a comprehensive range of Hyd. Hose Cutting Machine, L.P. Hose Crimping M/c., Hydraulic Hose Skiving Machine, Horizontal Hose Crimping Machine, Vertical Crimping Machine.

Our range is demanded in the market for features like optimum strength, high efficiency and longer service life. Owing to their quality features, these are extensively used in automobile and engineering sectors. We have developed a sophisticated manufacturing unit, which is equipped with modern tools and machines.



www.devanshi.co.in

"I conside each Customer as a **Family Member** who deserves nothing but the **Best Service**"



HYDRAULIC HOSE SKIVING MACHINE



www.devanshi.co.in

Separate The Cover Rubber From Hydraulic Hose.

The ID of Hydraulic Hose Could Be
[1/4" To 2"] 6mm To 51mm, R2 to 4SP/4SH.

MODEL: DHI - 51S

TECHNICAL PARAMETERS		
Cutting range	1/4" To 2" R2 to 4SP / 4SH	
Voltage	220V / 440V AC	
Power	0.50 Hp / 0.37 Kw	
Measurement	L500 x W500 x H1100mm	
Weight (Approx.)	125 Kg	
Skiving Tools	10 Sets	



Features of Hose Skiving Machine

- Easy Operating and Portable
- Stable and Durable
- Fast Speed And High Efficiency
- Low Noise And Low Maintenance Cost
- High Quality And Reasonable Price

MODEL: DHI - 28ED

TECHNICAL PARAMETERS Capacity Hose Size (ID) 1/4" To 2" R2 11/2" 4SH Max. Opening (mm) Die Size +50 Work Head Through Bore φ 125mm Crimping Force (T) 2800KN / 280T Cycle Time 45 Sec. max. Motor HP 3HP / 440V AC Controls Digital Control Die Segment 1/4" to 2" (9 Nos.) Overall Dimension (WXLXH) 450 x 650 x 750 mm Weight (Approx.) 250 Kg. Push Button having & AUTO Mode of Operation cycle with Multi Degassing

HORIZONTAL HYDRAULIC HOSE CRIMPING MACHINE



HORIZONTAL HOSE CRIMPING MACHINE



www.devanshi.co.in

MODEL: DHI - 32 ED

TECHNICAL PARAMETERS	
Capacity Hose Size (ID)	1/4" to 3" R2
	2" 4SH
Max. Opening (mm)	Die Size +55
Work Head Through Bore	φ 165mm
Crimping Force (T)	3200KN/320T
Cycle Time	45 Sec. Max.
Motor (HP)	7.5 HP / 440V AC
Controls	Digital Control
Die Segments	½" to 3" (11 Nos.)
Master Die Shoe Length	125 mm
Overall Dimension (WxLxH)	450 X 850 X 850 mm
Weight (Approx.)	450 Kg.
Mode of Operation	Push Button having & AUTO cycle with Multi Degassing

MODEL: DHI - 37 ED

TECHNICAL PARAMETERS	
Capacity Hose Size (ID)	1/4" To 4" R2
	2" 6 Wire
Max. Opening (mm)	Die Size +55
Work Head Through Bore	215 mm
Crimping Force (T)	370T / 3700 KN
Cycle Time	45 Sec. max.
Motor HP	10 HP / 440V AC
Controls	Digital Control
Die Segment	1/4" to 4" [14 Nos.]
Overall Dimension (WXLXH)	550 x 950 x 950 mm
Weight (Approx.)	700 Kg.
Mode of Operation	Push Button having & AUTO cycle with Multi Degassing

HORIZONTAL HYDRAULIC HOSE CRIMPING MACHINE



HORIZONTAL HOSE CRIMPING MACHINE



www.devanshi.co.in

MODEL: DHI - 21 ED

TECHNICAL P	ARAMETERS
Capacity Hose Size (ID)	1/4" To 1" R2
	3/4" 4SH
Max. Opening (mm)	Die Size +40mm
Work Head Through Bore	85 mm
Crimping Force (T)	200T / 2000KN
Cycle Time	45 Sec. max.
Motor (HP)	2 HP / 440V AC
Controls	Digital Control
Die Segments	1/4" to 1" [6 Sets]
Master Die Shoe Length	80mm
Overall Dimension (WxLxH)	400 x 550 x 600mm
Weight (Approx.)	150 Kg.
Mode of Operation	Push Button having & AUTO cycle with Multi Degassing

MODEL: DHI - 21 V

TECHNICAL PARAMETERS

Capacity Hose Size (ID) 1/4" to 2" R2

1.1/4" R13

Max. Opening (mm) Die Size +24

Crimping Force (T) 300

Cycle Time 45 Sec. Max.

Motor (HP) 2 HP / 440V AC

Controls Micro Meter

Dei Segments 1/4" to 2" (9 Nos.)

Master Die Shoe Length 100

Overall Dimension (WxLxH) 720 x 450 x 1050mm

Weight (Approx.) 250 Kg.

VERTICAL HOSE CRIMPING MACHINE



LOW PRESSURE HOSE CRIMPING MACHINE



MODEL: DHI - 50 L

TECHNICAL PARAMETERS	
Capacity Hose Size (ID)	1/4" to 3/4" R3, R6, P.V.C.
Max. Opening (mm)	ф 40mm
Work Head Through Bore	ф 40mm
Crimping Force (T)	5 TONS
Cycle Time	10 Sec. Max.
Motor (HP)	1 HP / 440V AC
Controls	Automatic Control
Overall Dimension (WxLxH)	600 x 400 x 800mm
Weight (Approx.)	125 Kg

MODEL: DHI - 11T

TECHNICAL PARAMETERS	
Pressure range	Up To 900 Bar
Max opereting	900 Bar [13000 psi]
Testing force	Up to 4.4 GPM
Out Put Pot	½" Bsp Singale
Application	Industrial Hose Pipe
Test precision	10 Kg
Operate mode	Semi Automatic Control
Motor power	1.5 Kw
Voltage	440V Ac. 50HZ
Dimension	450 x 550 x 600mm
Weight (Approx.)	125 kg

Product Description:

- Easy to operate
- Come with oil and water as testing media
- Available with extra burst apartment
- Come with manual and control mode
- Available in customized designs and specifications.

HYDRAULIC HOSE TESTING MACHINE



LOW PRESSURE HOSE CRIMPING MACHINE



www.devanshi.co.in

MODEL: DHI - 65L

TECHNICAL PARAMETERS		
Crimping range	3/8" To 1" R6 , R3, P.V.C	
Max opening	65mm	
Crimping force	8T/ 800kN	
Cycle Time	10 Sec. Mex.	
Crimp precision	0.01mm	
Operate mode	Automatic Control	
Motor power	1.5 Kw	
Voltage	440V Ac. 50HZ	
Dimension	800 x 450 x 1100mm	
Weight (Approx)	135kg	



HOSE CUTTING MACHINE

MODEL: DHI - 51 C

TECHNICAL PARAMETERS

Cutting Capacity upto 2" R2 & 1½" 4SH

Blade 10" OD, High Speed Steel

Motor 3 HP / 440V AC

Smoke Free Cutting | Dust Free Cutting

Manufacturers of:

- Hydraulic Hose Skiving M/c.
- Horizontal Hydraulic Hose Crimping M/c.
- Horizontal Hose Crimping M/c.
- Low Pressure Hose Crimping M/c.
- Vertical Hose Crimping M/c.





748/2, G.I.D.C. Estate, Makarpura, VADODARA - 390 010. Gujarat, INDIA.



+91 98250 25036 +91 76980 01171



info@devanshi.co.in devanshihyd@gmail.com



www.devanshi.co.in www.devanshielectromech.com